

**INDUSTRIAL RAW MATERIALS CORP.**

645 MADISON AVENUE NEW YORK, N.Y. 10022 • TELEPHONE (212) 688-8080

CABLE: INDRAW NEW YORK

FAX 212-759-3696

E-MAIL: IRMWAX@AOL.COM

MATERIAL SAFETY DATA SHEET

This Material Safety Data Sheet contains environmental, health and toxicology information for your employees. Please make sure this information is given to them. It also contains information to help you meet community right-to-know/emergency response reporting requirements under SARA Title III and many other laws. If you resell this product, this MSDS must be given to the buyer or the information incorporated in your MSDS. Discard any previous edition of this MSDS.

This revision updates Section 1 (Product Identification) Date: January 31, 2004

1. PRODUCT IDENTIFICATION

A HAZARD WARNING IS NOT REQUIRED FOR THIS PRODUCT UNDER OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200)

MATERIAL IDENTIFICATION

| | | |
|-----------------------------|--------------------|--------------|
| Name: INDRAWAX 250-S | Composition | CAS # |
| | Slack wax, | 64742-61-6 |
| | Solvent dewaxed | |

Synonyms

Paraffin Wax

Product use: Multiple uses.

Chemical Family

Petroleum Hydrocarbon

Transportation Emergency Phone
(212) 688-8080

2. OSHA HAZARD DETERMINATION

**INDUSTRIAL RAW MATERIALS CORP.**

645 MADISON AVENUE NEW YORK, N.Y. 10022 • TELEPHONE (212) 688-8080

CABLE: INDRAW NEW YORK

FAX 212-759-3696

E-MAIL: IRMWAX@AOL.COM

The material is not hazardous as defined by OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Refer to Section XI of this MSDS for federal and state regulatory information.

Hazardous Ingredients: None

Hazardous Physical Properties: None

| | |
|---|---|
| EXPOSURE LIMIT FOR TOTAL PRODUCT | BASIS: OSHA Regulation 29 CFR |
| 2 mg/m ³ for wax fumes in air for an 8-hour workday. | 1910.1000 and by the American Industrial Hygienists (ACGIH) |

3. PHYSICAL DATA

| | |
|---------------------------|---|
| Appearance and Odor | Specific Gravity (H ₂ O = 1) |
| Translucent solid | 0.82 – 0.84 |
| Slight hydrocarbon odor | |
| Boiling Point/Range | % Volatile (by volume) |
| 635 F | Negligible |
| Vapor Pressure | Solubility in Water |
| < 1 mm Hg @ 100F | Negligible |
| Vapor Density (Air = 1.0) | Evaporation Rate |
| > 1 | Negligible |
| Melting Point D-127 | Volatile Organic Content |
| 115-128 Degrees F | Not determined |
| Flash point D-92 | |
| 380 Degrees F minimum | |

4. REACTIVITY DATA

Hazardous Decomposition Materials: Hazardous gases/vapors produced are carbon dioxide, incomplete combustion may produce carbon monoxide.

Conditions to Avoid: Strong oxidizing materials, heat, flame.

Hazardous Polymerization: Will not occur.

5. FIRE PROTECTION



INDUSTRIAL RAW MATERIALS CORP.

645 MADISON AVENUE NEW YORK, N.Y. 10022 • TELEPHONE (212) 688-8080

CABLE: INDRAW NEW YORK

FAX 212-759-3696

E-MAIL: IRMWAX@AOL.COM

FLASH POINT: 380° F Min. D-92
AUTOIGNITION: NDA
FLAMMABILITY LIMITS (% by volume in air): Lower: NDA Upper: NDA
EXTINGUISHING MEDIA:

CO₂, dry chemical, foam and water fog.

NFPA Ratings: Health 1; Flammability 1; Reactivity 1; Special NDA;
HMIS RATINGS: Health 1; Flammability 1; Reactivity 1; other NDA; (Least-0, Slight-1, Moderate-2, High-3, Extreme-4).

These values are obtained using the guidelines or published evaluations prepared by the National Fire Protection Association or, if applicable, the National Paint and Coating Association, and do not necessarily reflect the hazard document **read label** before using this product.

FIRE FIGHT PROCEDURES:

In case of fire, smother flames and turn off heat source. **DO NOT** use water to extinguish wax fires as the water may boil violently causing an explosion of hot wax.

COMBUSTION PRODUCTS:

Normal combustion forms carbon dioxide and water vapor; incomplete combustion can produce carbon monoxide.

6. STORAGE, HANDLING AND REACTIVITY

Hazardous Decomposition Products: NDA

Stability: Stable

Hazardous Polymerization: Polymerization will not occur

Incompatibility: May react with strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

Special Precautions: **READ AND OBSERVE ALL PRECAUTIONS ON PRODUCT LABEL.**



INDUSTRIAL RAW MATERIALS CORP.

645 MADISON AVENUE NEW YORK, N.Y. 10022 • TELEPHONE (212) 688-8080

CABLE: INDRAW NEW YORK

FAX 212-759-3696

E-MAIL: IRMWAX@AOL.COM

7. IMMEDIATE HEALTH EFFECTS

EYE CONTACT

The cool material is not expected to cause eye irritation. However, thermal burns may result from contact with the hot material. The degree of the injury will depend on the amount of material that gets into the eye and the speed and thoroughness of the first aid treatment. Signs and symptoms may include pain, tears, swelling, redness and blurred vision.

SKIN IRRITATION

If this material is used at elevated temperatures, skin contact can be minimized by wearing protective clothing.

RESPIRATORY PROTECTION

No special respiratory protector is normally required. However, if operating conditions create high airborne concentrations, the use of an approved respirator is recommended.

VENTILATION

No special ventilation is usually necessary. However, if operating conditions create high airborne concentrations of this material, special ventilation may be needed.

8. EMERGENCY AND FIRST AID INFORMATION

Eyes: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.

Skin: If skin is exposed in hot wax, immediately cool by applying cold water. Do not attempt to remove material. Consult a physician.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.



INDUSTRIAL RAW MATERIALS CORP.

645 MADISON AVENUE NEW YORK, N.Y. 10022 • TELEPHONE (212) 688-8080

CABLE: INDRAW NEW YORK

FAX 212-759-3696

E-MAIL: IRMWAX@AOL.COM

9. SPILL, LEAK AND DISPOSAL INFORMATION

In case of Spill or Leak: Protect from ignition sources. Contain spill immediately in smallest possible areas. Material will solidify as it cools from a molten state. Recover as much of the product as possible by shovel or mechanical means. Non-recoverable product, contaminated soil, debris and other materials should be placed in proper containers for ultimate disposal. Avoid washing, draining or directing material to storm or sanitary sewers.

NOTE: Review **FIRE AND EXPLOSION HAZARDS** before proceeding with clean up. Use appropriate **PERSONAL PROTECTIVE EQUIPMENT** during clean up.

Waste Disposal Method: Recycle as much of the recoverable product as possible. Treatment, storage, transportation and disposal must be in accordance with applicable Federal, State/Provincial and Local Regulations.

10. ECOLOGICAL INFORMATION

This wax is not expected to adversely effect the environment.

11. PRECAUTIONARY MEASURES

Respiratory Protection: None normally required except under unusual circumstances such as described in Section V.

Ventilation: Normal shop ventilation.

Protective Gloves: Impervious, insulated while handling hot product.

Eye Protection: Goggles if handling hot product.

Other Protective Equipment: As needed to protect against hot product.

Safety Precautions: Normal precautions for handling hot, molten liquid or solutions.



INDUSTRIAL RAW MATERIALS CORP.

645 MADISON AVENUE NEW YORK, N.Y. 10022 • TELEPHONE (212) 688-8080

CABLE: INDRAW NEW YORK

FAX 212-759-3696

E-MAIL: IRMWAX@AOL.COM

12. TOXICOLOGICAL INFORMATION

Immediate (acute) effects:

Not applicable for molten product as application in liquid form would result in burn.

Delayed (subchronic & chronic) effects:

Not determined.

Other data:

Not determined.

13. TRANSPORTATION INFORMATION

US DOT Proper shipping name: Elevated temperature liquid, N.O.S. (molten wax)

US DOT Hazard class: 9, Miscellaneous hazardous material.

US DOT ID number: UN 3257

US DOT Packing group: III

The above only applies to materials whose temperature is at or above 212 degrees fahrenheit at the time of loading. Temperatures under 212 degrees fahrenheit, the material is not DOT regulated.

14. REGULATORY INFORMATION

Federal Regulation

CERCLA, 40 CFR 302 – Not applicable

**SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986, TITLE III
SECTIONS 302, 304, 312, 313**

SECTION 302/304 – Extreme Hazardous Substances (40 CFR 355) The material does not contain extremely hazardous substances at greater than 1.0% concentration; however, it is possible that this material may contain extremely hazardous substances at a lower concentration so that a large enough spill could warrant an Emergency Release Report under Section 304.



INDUSTRIAL RAW MATERIALS CORP.

645 MADISON AVENUE NEW YORK, N.Y. 10022 • TELEPHONE (212) 688-8080

CABLE: INDRAW NEW YORK

FAX 212-759-3696

E-MAIL: IRMWAX@AOL.COM

SECTION 311/312 – MSDS and Chemical Inventory Reporting Requirements (40 CFR 370)

The material should be reported under the following EPA hazard categories:

- | | |
|--|---|
| <input type="checkbox"/> Immediate (Acute) Health Hazard | <input type="checkbox"/> Sudden Release of Pressure |
| <input type="checkbox"/> Delayed (Chronic) Health Hazard | <input type="checkbox"/> Reactive |
| <input type="checkbox"/> Fire | <input type="checkbox"/> Not Applicable |

NOTE: See Section II for the concentration of any ingredients classified as hazardous by OSHA.

Section 313 – List of Toxic Chemicals (40 CFR 372)

The material does not contain chemical (s) at a level of 1.0% or greater (0.1% for carcinogens) on the list of toxic chemicals and subject to toxic chemical release reporting requirements.

TOXIC SUBSTANCES CONTROL ACT (TSCA), 40 CFR 710

This material is in the TSCA inventory of Chemical Substances and/or is otherwise in compliance with TSCA.

RESOURCE CONSERVATION AND RECOVERY ACT (RCRA), 40 CFR 261, SUBPART C AND D

The material, when discarded or disposed of, is not specifically listed as a hazardous waste in Federal regulations; however, it could be considered hazardous if it meets criteria for being toxic, corrosive, ignitable or reactive according to U. S. EPA definitions (40 CFR 261). Additionally, it could be designated as hazardous according to state regulations. This material could also become a hazardous waste if it is mixed with or comes in contact with a listed hazardous waste. If such contact or mixing occurs, check 40 CFR 261 to determine whether it is a hazardous waste. If it is a hazardous waste, Regulations 40 CFR 262, 263, 264 and 268 may apply.

FEDERAL WATER POLLUTION CONTROL ACT, CLEAN WATER ACT, 40 CFR 116 SECTION 311



INDUSTRIAL RAW MATERIALS CORP.

645 MADISON AVENUE NEW YORK, N.Y. 10022 • TELEPHONE (212) 688-8080

CABLE: INDRAW NEW YORK

FAX 212-759-3696

E-MAIL: IRMWAX@AOL.COM

The material contains the following ingredient (s) which is considered hazardous in navigable waters.

Ingredient

Reportable Quantity

Petroleum Hydrocarbon

Film or sheen upon or discoloration of the water surface or adjoining shoreline.

HAZARDOUS MATERIALS TRANSPORTATION REGULATIONS, 49 CFR 171 – 178

Not Applicable.

STATE REGULATIONS

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986 (“PROPOSITION 65”)

The material does not contain ingredient(s) subject to the Act.

PENNSYLVANIA WORKER AND COMMUNITY RIGHT TO KNOW ACT.

The material contains the following hazardous substances:

- | | | | |
|-------------|---|---|---------------------------------------|
| Categories: | H | = | Hazardous Substance (> 1.0%) |
| | S | = | Special Hazardous Substance (> 0.01%) |
| | E | = | Environmental Hazard (> 1.0%) |

Non-hazardous ingredient (s) information is withheld as trade secret in accordance with Section 11 (eleven) of Pennsylvania Worker and Community Right to Know Act.

A. SARA TITLE III

Title III Section 302/304 Extremely Hazardous Substance:

| | | | |
|------------------|----------------|-------------------------|------------------|
| <u>Component</u> | <u>CAS No.</u> | <u>Percent RO (Lbs)</u> | <u>TPO (Lbs)</u> |
| None | | | |

CERCLA Section 102 (a) Hazardous Substance

| | | |
|------------------|----------------|-------------------------|
| <u>Component</u> | <u>CAS No.</u> | <u>Percent RO (Lbs)</u> |
| None | | |

Title III Section 311 Hazard Categorization

| | | | | | |
|-------|---------|------|----------|----------|----------------|
| Acute | Chronic | Fire | Pressure | Reactive | Not Applicable |
|-------|---------|------|----------|----------|----------------|



INDUSTRIAL RAW MATERIALS CORP.

645 MADISON AVENUE NEW YORK, N.Y. 10022 • TELEPHONE (212) 688-8080

CABLE: INDRAW NEW YORK

FAX 212-759-3695

E-MAIL: IRMWAX@AOL.COM

X

Title III Section 313 Toxic Chemicals

| Component | CAS No. | Percent |
|-----------|---------|---------|
| None | | |

B. WHMIS CLASSIFICATION
NA

C. MICHIGAN CRITICAL MATERIALS
No critical materials present.

Information contained herein is correct and accurate, to the best of Industrial Raw Materials Corporation's knowledge, however, IRM makes no warranty, oral or written, expressed or implied, of merchantability or fitness for a particular purpose, regarding this product or its use. Purchaser assumes all risks of use, application and handling.

INDUSTRIAL RAW MATERIALS CORP.
