INDUSTRIAL RAW MATERIALS LLC
112 West 56th Street, New York, NY 10019 Telephone: (212) 688-8080
Fax: (212) 759-3696
Email: sales@irmwax.com Website: www.irmwax.com

INDRAWAX 2325-SC

Indrawax 2325-SC is a low-range melting point petroleum scale wax. It has no sulphur odor or excessive solvent smell. Its inherent natural oxidation stability helps prevent color degradation in storage under normal handling temperatures and practices.

Indrawax 2325-SC can be used in candle wax blends, adhesives, inks, packaging materials, tire and cable filler, and other applications.

SPECIFICATIONS

Property	Method	Min	Max	Typical
Melting point, °F (°C)	D-87	-	-	123.0 (50.5)
Congealing point, °F (°C)	D-938	113.0 (45.0)	122.0 (50.0)	121.0 (49.5)
Penetration @ 77°F, dmm	D-1321	-	-	36
Oil content, wt%	D-721	-	5.0	3.0
Color, Saybolt	D-156	+15	-	+20
Viscosity @ 210°F, cSt	D-445	2.7	3.45	3.0
Flash point PMCC,°F (°C)	D-93	374 (190)	-	402 (205)

Every care has been taken in the presentation of this information. To the extent permitted by applicable law, all warranties and/or representations, express or implied, as to the accuracy of the information are disclaimed, and no liability is accepted for the accuracy or completeness of the same.
Industrial Raw Materials LLC.