



INDUSTRIAL RAW MATERIALS LLC

112 West 56th Street, New York, NY 10019 Telephone: (212) 688-8080

Fax: (212) 759-3696

Email: sales@irmwax.com Website: www.irmwax.com

INDRAWAX 6643

Indrawax 6643 is a mid-range melting point petroleum scale wax. The wax is a translucent crystalline material in the solid state and a yellow clear liquid when molten. It is derived from petroleum via a carefully controlled refining process and is primarily comprised of a mixture of straight chain normal paraffin and branched, iso-paraffin hydrocarbons.

Indrawax 6643 can be used in candle wax blends, wax emulsions, wood and fibre board sizing, de-dusting for roofing granules, roads, fertilizer, glass wool, and textile treating, and other applications.

SPECIFICATIONS

Property	Method	Min	Max	Typical
Melting point, °F (°C)	D-87	140.0 (60.0)	154.0 (67.8)	-
Penetration @ 77°F, dmm	D-1321	-	-	75
Oil content, wt%	D-721	-	20.0	-
Color, ASTM	D-1500	-	3.0	-
Viscosity @ 210°F, cSt	D-445	6.8	11.0	-
Flash point COC, °F (°C)	D-92	450 (232)	-	-

Every care has been taken in the presentation of this information. To the extent permitted by applicable law, all warranties and/or representations, express or implied, as to the accuracy of the information are disclaimed, and no liability is accepted for the accuracy or completeness of the same.

Industrial Raw Materials LLC.